



Ensure maximum operator safety with this Emergency Stop (E-Stop) Control Station, designed for industrial automation, machinery, and process control applications. Featuring a push-twist emergency stop actuator with a visual indicator, this IP-rated safety station allows operators to immediately halt machine operations in critical situations.

Equipped with One Normally Closed contact, this e-stop control station ensures fail-safe functionality and compliance with emergency safety regulations. The enclosure includes vertical knockouts, providing easy wiring access for seamless integration into control panels and machinery systems.

Built for industrial reliability, this emergency stop control station is shock-resistant, vibration-proof, and designed for long-term durability in harsh environments. Ideal for manufacturing plants, conveyor systems, automated machinery, and factory automation setups.

Key Benefits:

- Push-Twist Emergency Stop with Visual Indicator – Enhances safety by providing clear status visibility and immediate operation halt.
- One Normally Closed Contact – Ensures fail-safe emergency stop functionality for machine control systems.
- Durable IP-Rated Enclosure – Designed for harsh industrial environments with moisture and dust protection.
- Vertical Knockouts for Easy Wiring – Allows quick and efficient installation in control panels and machinery.
- Industrial-Grade Construction – Built to withstand impact, vibration, and demanding operating conditions.
- Compliant with Safety Standards – Meets emergency stop requirements for automation, manufacturing, and process control applications.

Technical specifications

Type	
Product No.	EP1FAC05
Style	Mushroom Head Actuator (Push Turn Type)
Color	Red, Grey and Black
Legend	Twist On / Push Off
Contact	1 NC
Safety	Fully insulated to hose electrical & electronic equipment w.r.t. protection against electric shock.
Material	Bottom Cover: Tough, Impact resistant & fire retardant ABS. Top Cover: Tough, Impact resistant & fire retardant ABS. Gasket: Nitrile rubber, which is good resistant to Oil & acids. Screws: Half threaded Self tapping Cold Forged Screws with blaco-dising.
Single - Dimensions	65x55x33 mm
Screw Size for Wall Mounting	M3.5 mm Insertion of screws directly through base cover.
Temperature Range	Long term exposure to temperatures above 70° C should be avoided. No significant change in impact strength is noticed up to -20° C.
Degree of Protection	NEMA 4 / IP 65

