

POLM Series

Applications

Partition terminal boards are used as supplementary terminal blocks for phase expansion or neutral expansion inside electrical panels.

They are also known as equipotential terminal boards because they are used as equipotential nodes in distribution control units to collect the Earthing system.

General characteristics

- Protected terminal blocks, 7, 11, or 15 holes
- Mounting on mounting rails PR/3 according to IEC 60715, TH/35 type or with screws on walls
- Insulation voltage 500 V (according to IEC 60947-1)
- Conformity with EU Low Voltage Directive 2006/95/EC

Materials

- CW 614N Brass, polyamide (coloured products), polycarbonate (transparent products)
- Zinc-plated steel screws with combined single-slot


Cat. No.	Type	Colour	rated cross-section (mm ²)	Rated current	Number of holes
QPOL1203	POLM.1215	Grey	12 x 1.5 2 x 2.5 1 x 16	80 A	The hole with diameter 16 mm ² has screw clamp
QPOL1205	POLM.1215/BLU	Blue	12 x 1.5 2 x 2.5 1 x 16	80 A	The hole with diameter 16 mm ² has screw clamp
QPOL1204	POLM.1215/TE	Green	12 x 1.5 2 x 2.5 1 x 16	80 A	The hole with diameter 16 mm ² has screw clamp



Spring-clamp



Spring-clamp



Spring-clamp