


Certifications	
	
Material	
Screw	M3 Steel Zinc Plate
Wire Cage	Copper Alloy, Nickel Plated
Pin/Plate	Copper Alloy, Tin plated
Housing	PA 66 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	14A
Wire Range	30-14AWG
Contact Resistance	20mΩ
Insulation Resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1Min
Mechanical	
Temperature Range	-30°C~+120°C
Torque	0.5Nm(4.4 lb/in)
Strip Length	6mm (0.24-0.28")
Size	
Pitch	5/5.08mm
Poles	2P-24P

Item	Positions	Length (mm)
CIA5/5.08-2VE	2	10 / 10.16
CIA5/5.08-3VE	3	15 / 15.24
CIA5/5.08-4VE	4	20 / 20.32
CIA5/5.08-5VE	5	25 / 25.4
CIA5/5.08-6VE	6	30 / 30.48
CIA5/5.08-7VE	7	35 / 35.56
CIA5/5.08-8VE	8	40 / 40.64
CIA5/5.08-9VE	9	45 / 45.72
CIA5/5.08-10VE	10	50 / 50.8
CIA5/5.08-11VE	11	55 / 55.88
CIA5/5.08-12VE	12	60 / 60.96
CIA5/5.08-13VE	13	65 / 66.04
CIA5/5.08-14VE	14	70 / 71.12
CIA5/5.08-15VE	15	75 / 76.2
CIA5/5.08-16VE	16	80 / 81.28
CIA5/5.08-17VE	17	85 / 86.36
CIA5/5.08-18VE	18	90 / 91.44
CIA5/5.08-19VE	19	95 / 96.52
CIA5/5.08-20VE	20	100 / 101.6
CIA5/5.08-21VE	21	105 / 106.68
CIA5/5.08-22VE	22	110 / 111.76
CIA5/5.08-23VE	23	115 / 116.84
CIA5/5.08-24VE	24	120 / 121.92