







<b>Technical drawing</b>																					
<b>Product description</b>																					
Connector type				DIN valve connectors				DIN valve connectors				DIN valve connectors									
Conforms to				EN175301-803				EN175301-803				EN175301-803									
Construction type				C				C				C									
Part number				<b>P1TZ2L01</b>		<b>P1TZ2L02</b>		<b>P1TZ2L03</b>		<b>P1TZ2DL1</b>		<b>P1TZ2DL2</b>		<b>P1TZ2DL3</b>		<b>P1TZ2VL1</b>		<b>P1TZ2VL2</b>		<b>P1TZ2VL3</b>	
Description				Square micro connector P1 series complete with gasket and fixing screw. Connector with electronic.				Square micro connector P1 series complete with gasket and fixing screw. Connector with electronic.				Square micro connector P1 series complete with gasket and fixing screw. Connector with electronic.									
Contacts spacing				8mm				8mm				8mm									
Number of contacts				2poles + P.E.				2poles + P.E.				2poles + P.E.									
Earth positioning				H.6 (turnable)				H.6 (turnable)				H.6 (turnable)									
Housing colour				Transparent				Transparent				Transparent									
Housing height				26mm				26mm				26mm									
Cable gland				PG7				PG7				PG7									
Gasket type				Profiled NBR gasket				Profiled NBR gasket				Profiled NBR gasket									
<b>Technical data</b>																					
Type of termination				Screw contacts				Screw contacts				Screw contacts									
Contact screw torque				0.25 N*m				0.25 N*m				0.25 N*m									
Rated voltage				24V AC/DC		115V AC/DC		230V AC/DC		24V DC		115V DC		230V DC		24V AC/DC		115V AC/DC		230V AC/DC	
Circuit type				Bipolar led				Led + Diode(1A)				Bipolar Led + Varistor									
Led colour				Red				Red				Red									
Suitable cable				ø cable 4-6mm				ø cable 4-6mm				ø cable 4-6mm									
Central fixing screw				M2.5 L=28mm				M2.5 L=28mm				M2.5 L=28mm									
Central fixing screw material				Iron+Zinc plated				Iron+Zinc plated				Iron+Zinc plated									
Central screw torque				0.4 N*m				0.4 N*m				0.4 N*m									
<b>Packaging</b>																					
Qty/Box				100pcs / box				100pcs / box				100pcs / box									
<b>Other accessories options</b>																					
See accessories section																					
<b>Notes:</b>				Connector available with different led colour				Connector available with different led colour				Connector available with different led colour									